

Instruction Sheet Taco Swing 120130

Store these instructions along with the enclosed maintenance checklist in a safe place. You may also access them on our website.

Replacement Cover 120131



Take time to familiarize yourself with the use and maintenance of this equipment before using. Please file this Instruction Sheet in an accessible location. The Instruction Sheet must be read and familiar to anyone who is using Southpaw Enterprises Equipment.

IMPORTANT: Please check equipment immediately for any damage that may have resulted during shipping. If any damage has occurred, please contact Southpaw Enterprises, Inc. immediately.

Warning: Failure to properly install a forged steel eyebolt (1/2" or 5/8") may result in serious injury or death. If you have any questions about the installation of the forged steel eyebolt, please contact Southpaw Enterprises

MATERIALS LIST:

- 1 Taco Swing
- 1 Instruction Sheet
- 2 Safety Snaps

- 1 Safety Snap Instruction Sheet
- 1 Maintenance Checklist

INSTRUCTIONS FOR USE:

- The Taco Swing may be suspended from a single suspension point for non-linear movement. Note: a Southpaw Safety Rotational Device (# 2000) must be used with any rotational movement to prevent damage to the equipment.
- Use the Southpaw Height Adjuster (# 5000) to raise or lower the Taco Swing to the appropriate height.

WEIGHT LIMIT: 170 lbs.

SPACE REQUIREMENTS: Use caution to keep a minimum of 6 foot clear distance from walls and other obstacles.

MAINTENANCE CHECKLIST:

The following wear points should be checked on a monthly basis and recorded on the checklist enclosed.

- Check seams for rips or tears. If rips or tears are found, discontinue use immediately until repaired.
- Check ropes for loose or missing splice locks.* If loose or missing splice locks are found, discontinue use until
 repaired.
- Check wood for cracks or splinters. If cracks are found, discontinue use immediately. Splinters may be sanded smooth and refinished with clear lacquer.
 - * A splice lock is the metal clip near the end of the ropes.
- Check Safety Snaps for wear (see Safety Snap Instruction Sheet).

MATTING PRECAUTIONS:

- Always use appropriate matting.
- Crash mats and wall mats must be used with all hanging equipment.

CLEANING INSTRUCTIONS:

Check with your infectious disease department before using these procedures.

- Check for client allergies first.
- Cover is machine washable using cold or warm water and mild detergent. Tumble dry LOW heat.
- The body of the Taco Swing may be removed for cleaning by unzipping the zippers on each side.

STORAGE PROCEDURES:

• Store out of direct sunlight.

REPLACEMENT COVERS:

- Replacement covers (# 120131) are available. You may want to have an extra cover to use while one is being cleaned.
- To put on a new cover, unzip the cover and remove from the frame. Reverse steps to install.

CAUTION

- ♦ Check ceiling eye bolt for wear and movement. Use a Southpaw Safety Rotational Device to prevent abnormal wear.
- ♦ Floor mats of proper thickness should be positioned properly under and around all suspended equipment.

Safety Precautions - The safety of your clients is dependent on the appropriate choice of activity to match, yet challenge their physical abilities. Use appropriate spotting / safety techniques. In addition, the layout of your activity area, proper installation and maintenance of your equipment is critical. Southpaw equipment is not intended for recreational or outdoor use. Under no condition should this equipment be used without proper supervision.

This sheet is for example only. It is not meant to, in any way, replace local, county, state, or Federal standards. Be aware - it is your responsibility to find all pertinent safety information that pertains to your facility.

If you have any questions or comments, please call or write
Southpaw Enterprises, Inc.
P.O. Box 1047, Dayton, Ohio 45401 -1047
Toll Free - (800) 228-1698
Please visit us @ www.southpae.com
© 2019 Southpaw Enterprises, Inc.