



southpaw enterprises, inc.®

Store these instructions in a safe place or you may access them on our website.

Instruction Sheet

Play Loft Ball Pit 150210



Take time to familiarize yourself with the use and maintenance of this equipment before using. Please file this Instruction Sheet in an accessible location. The Instruction Sheet must be read and familiar to anyone who is using Southpaw Enterprises Equipment.

IMPORTANT: Please check equipment immediately for any damage that may have resulted during shipping. If any damage has occurred, please contact Southpaw Enterprises, Inc. immediately.

MATERIALS LIST:

- 4 - Ball Pit Walls
- 1 - Ball Pit Floor with hook fastener on edges.
- 1 - Instruction Sheet
- 1 - Maintenance Checklist

ASSEMBLY PROCEDURE:

- Make sure that the Play Loft floor mat is in place and secured to the bottom of the legs with the hook and loop fastener.
- Notice that each wall section has a 2" strip of hook fastener sewn to the inside of the wall on one end. This strip will mate to the loop material on the ends of the adjoining wall section.
- The bottom of each wall section has loop material that will mate with the hook fastener on the edge of the Ball Pit Floor to secure the bottom of the walls.
- The wall sections will be properly positioned with the Southpaw label on the outside and at the bottom of each wall section. This will have the 2" hook strip on the inside of the wall.
- Step 1. Start by positioning the first wall section (with the label facing out, at the bottom) inside the legs with the end of the wall with the hook strip tight into the corner of the leg.
- Step 2. Position the second wall section so that the loop material on the end of the wall will mate with the 2" hook strip on the inside of the first wall section.
- Step 3. Position the third wall section so that the loop material on the end of the wall will mate with the 2" hook strip on the inside of the second wall section.
- Step 4. Position the fourth wall section so that the hook and loop material will mate with the ends of the first and third walls.
- Step 5. (This step is easiest accomplished by two people). Raise all four walls (two people on opposite sides). While one person holds up the sides, the other person positions the Ball Pit Floor under the walls with the hook fastener on the edges facing up. Lower the walls on to the floor. Push down on the walls to connect the hook and loop fastener.

MAINTENANCE CHECKLIST:

All of the following wear points should be checked on a monthly basis and recorded on the checklist enclosed.

- Check seams for rips or tears. If rips or tears are found, discontinue use until repaired.

CLEANING INSTRUCTIONS:

Check with your infectious disease department before using these procedures.

- Check for client allergies first.
- Wipe with a damp cloth using soap and water or disinfectant.

Safety Precautions - The safety of your clients is dependent on the appropriate choice of activity to match, yet challenge their physical abilities. Use appropriate spotting / safety techniques. In addition, the layout of your activity area, proper installation and maintenance of your equipment is critical. Southpaw equipment is not intended for recreational or outdoor use. Under no condition should this equipment be used without proper supervision.

This sheet is for example only. It is not meant to, in any way, replace local, county, state, or Federal standards. Be aware - it is your responsibility to find all pertinent safety information that pertains to your facility.



Southpaw
Enterprises Inc.®

If you have any questions or comments, please call or write
Southpaw Enterprises, Inc.
P.O. Box 1047, Dayton, Ohio 45401 -1047
Toll Free - (800) 228-1698
Come see us on the World Wide Web at <http://southpawenterprises.com>