



SOUTHPAW®

Instruction Sheet

Interactive Marble Panel # 903303



Take time to familiarize yourself with the use and maintenance of this equipment before using. Please file this Instruction Sheet in an accessible location. The Instruction Sheet must be read and familiar to anyone who is using Southpaw Enterprises Equipment.

Store these instructions along with the enclosed maintenance checklist in a safe place.

You may also access them on our website.

IMPORTANT: Please check equipment immediately for any damage that may have resulted during shipping. If any damage has occurred, please contact Southpaw Enterprises, Inc. immediately.

MATERIALS LIST:

Marble Wall (903303) 6 - 1-1/2" Wood Screws (XH90430) Drill
2 - 2 x 4's (XW7100) Instruction Sheet 1/2" Drill Bit
4 Wall Anchors (XH90651) Maintenance Checklist

TOOLS NEEDED:



INSTALLATION:

Position 2" x 4" lengthwise level on the wall at top height where activity wall will be placed. Drill holes through 2 x 4's into wall. Set anchors and secure 2" x 4" to the wall. Set activity wall on 2" x 4", mark where the bottom of the activity wall is, remove activity wall. From the mark that has been made on the wall, mark another line 1/2" above that line and position 2" x 4" on the on the second mark, making certain it is level. Repeat above steps for mounting 2 x 4. Replace activity wall, secure wall to the 2" x 4" frame with three wood screws on the top and three wood screws on the bottom.

OPERATION:

Once the Marble Wall has been plugged in, follow instructions that came with 903111 Super Controller to pair device and begin interactive use. This unit must be used in conjunction with the Super Switch (item #903100) or the Power Cube (item #903105 or 903106) or One button Switch (903108) for use of interactive features.

MAINTENANCE CHECKLIST

✓All of the following wear points should be checked on a monthly basis and recorded on the checklist enclosed:

- Check the wood surface and edges for splinters. If found, discontinue use until repaired. You may repair it by sanding the area smooth with a medium grit sandpaper, and applying two coats of clear lacquer to the repaired area.
- Check all components to make certain they remain secured to activity wall.

MATTING PRECAUTIONS:

- Always use appropriate matting under and around equipment.


CLEANING INSTRUCTIONS

- Check with your infectious disease department before using these procedures.
- Check for client allergies first.
- Clean with a damp rag and a mild surface cleaning solution.
- Let air dry or wipe dry with a cloth.


Safety Precautions - The safety of your clients is dependent on the appropriate choice of activity to match, yet challenge their physical abilities. Use appropriate spotting / safety techniques. In addition, the layout of your activity area, proper installation and maintenance of your equipment is critical. Southpaw equipment is not intended for recreational or outdoor use. Under no condition should this equipment be used without proper supervision.

This sheet is for example only. It is not meant to, in any way, replace local, county, state, or Federal standards. Be aware - it is your responsibility to find all pertinent safety information that pertains to your facility.


Step-By-Step




Drill a 1/2" (Ø13mm) hole. Hold metal channel flat alongside plastic straps and slide channel through hole. Minimum clearance behind wall: 1-7/8" (48mm).



Hold ends of straps between thumb and forefinger and pull toward you until channel rests flush behind wall. Slide plastic cap along straps with other hand until flange of cap is flush with wall.



Snap straps at wall by pushing side to side, snapping off straps level with flange of cap.



Place item over flange. Insert bolt through item and tighten until flush against item, then stop.